

PRECISION BREW[™] Single Cup Pod Brewer



GRINDMASTER^{**}

CORPORATION





www.grindmaster.com

PRECISION BREW Your Cup.



Brew Control™

Adjustable brew strength control: Mild, Medium, Strong, and Tea, allows users to fine tune their flavor preference.

Dual Water System

Brewer can be plumbed into water line or manually filled.





See-through Water Reservoir

Reservoir is back-lit with bright blue LED to see water in reservoir.

Bright Feedback LEDs

Bright yellow LED alerts user when brewer is low on water (manual refill mode) and bright green LED alerts user when water is at correct brew temperature.



Brewer can be used with Pods ranging from 55 to 61mm and Pod weights ranging from 8.0 to 13.0 grams. Gourmet Pod holder available for heavier, larger Pods (Pods heavier than 10.5 grams).

12-Month Replacement Warranty (USA only*)

Brewer will be replaced for any material or workmanship defect for 12 months after purchase. Field serviceable unit beyond warranty - service parts available. * 12 month part replacement warranty (outside USA).





Easy Operation:

Step 1: Place a pod in the pod holder, push



Step 2: Place your cup under the drawer. Select a and lock the pod drawer into place. brew strength (mild, medium, strong, or tea).



Step 3: Press and release the BREW button.



Step 4: Enjoy your perfect cup of coffee or tea within one minute!



Designed for Serviceability.

Anti-scaling Water Tank Heater

Die-cast aluminum heater has two high-tech, baked-on, anti-scaling coatings to prevent corrosion.

Easy-Remove Hot Water Tank

Hot water tank can be easily removed by disconnecting electrical and water connections and removing two no-tool fastening pins.



0 6

Color Coded Plumbing Connections

Internal tubing connections are color-coded for ease of reconnection.

Cooling Fan

Cooling fan prolongs component life inside brewer and spreads the coffee aroma throughout the room.



External Control Board Connector

Allows field reprogramming without opening unit.

Patented Drawer Assembly



Drawer assembly rolls on permanently lubricated roller bearings. Drawer can be easily changed by the removal of one screw.

Accessories:

BREW

RENGT

Water Pump p/n 60568



Gourmet Pod Tray p/n 92835



Pod Holder Rack p/n 92836



Pod Waste Bin p/n 92837



Profit by the Cup

Small Office Revenue Potential

The untapped small office segment of the market has the potential to generate as much revenue as the existing OCS market.

| Number of small offices in the US (offices with 25 or fewer employees) | 11.5 M |
|---|----------|
| Daily Revenue Opportunity (average 10 cups/day/office @ \$0.25 cost/cup) | \$28.8 M |
| Annual Revenue Opportunity | \$7.2 B |

Market Opportunity

36% of the 42 million cups of coffee consumed in the office daily are purchased outside the office.

15M cups of coffee per day from outside office

27M cups of coffee per day from inside office

Why?

- Tastes better
- Large variety of flavors

Revenue Potential to Capture

| Annual Revenue (250 working days/year) | <u>\$950 M</u> |
|--|----------------|
| Daily Revenue (15M cups/day x \$0.25 cost/cup) | \$3.8 M |
| Number of cups brought from outside the office per day | 15 M |

Revenue that is currently being lost!


Source: Q2 Brand Intelligence

Gives Individual Flavor Selection

French Roast

Hazelnut

Kona Blend



Tropical Citrus Tea House Blend Chocolate Sumatra English Breakfast Tea Colombian French Vanilla

Green Tea



Earl Grey Tea Irish Cream Breakfast Blend Cappuccino



Model OPOD

Features

PrecisionBrewTM Innovative precision pod brewing and infusion technology provides the ideal cup every time

BrewControl[™]

Adjustable brew strength control allows users to fine tune their flavor preferences

Smartstop[™] Automatic Water Shutoff Water shuts off when pod drawer is open

Programmable Cup Size Control the volume of beverage dispensed into the cup

Stylish, high performance design

Dual Water System Brewer can be plumbed into a water line or manually filled

| Specification | Model OPOD | Model OPOD-E | |
|---|---------------------------|---|--|
| Electrical | 120V, 1300W, 10.8A | 230V, 1200W, 5.2A | |
| Frequency | 60 Hz | 50/60 Hz | |
| Water Inlet Pressure (plumbed units only) | 10-145 p | 10 - 145 psi | |
| Water Reservoir Capacity | 80 fl. oz. (2 | 80 fl. oz. (2.4 L) | |
| Hot Water Tank Capacity | 35 fl. oz. (* | 35 fl. oz. (1 L) | |
| Maximum Brewing Water Temperature | 200°F (93° | 200°F (93°C) | |
| Minimum Brewing Water Temperature | 185°F (85° | 185°F (85°C) | |
| Brewing Volume | Approx. 8 fl. oz. (237 ml | Approx. 8 fl. oz. (237 ml) (programmable) | |
| Dimensions (H x W x D) | | 14-1/4" (19" incl. reservoir lid upswing) H x 8-1/4" W x 14" D 36 cm (48 cm incl. reservoir upswing) x 21 cm x 36 cm | |
| Ship Dimensions (H x W x D) | | 16" H x 9-3/4" W x 15-3/4" D 41 cm x 25 cm x 40 cm | |
| Weight | 12 lbs. (5.4 | 12 lbs. (5.4 kg) | |
| Ship Weight | 15 lbs. (6.8 | 15 lbs. (6.8 kg) | |
| Listings | NSF, UL | NSF, CE | |

Specifications are subject to improvement or change without notice.





14"

(36 cm)

1[']4-1/4" (36 cm)

Side View

8-1/4'

(21 cm)

Front View

Grindmaster® Coffee Grinders and Brewers • PrecisionBrew™ Brewing Systems • Espressimo® Espresso Machines Crathco® Hot Beverage Dispensers • Crathco® Cold and Frozen Beverage Dispensers • AMW Coffee and Tea Systems Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500 (USA & Canada only) P.O. Box 35020 • Louisville, KY 40232 • USA

www.grindmaster.com • email: info@grindmaster.com



NS